



TECHNICAL SHEET

OLIVAL DA RISCA EXTRA VIRGIN OLIVE OIL 2023/2024

Versão: 03
Data: 28-02-2024
Página: 1/2
Referência: I228

OLIVAL DA RISCA EXTRA VIRGIN OLIVE OIL is an excellent olive oil with a fruity flavor, produced from several native olive varieties.

TYPE Extra Virgin Olive Oil

PROCESS CHARACTERISTICS The superior category olive oil OLIVAL DA RISCA EXTRA VIRGIN DEMETER is obtained from olives and it is extracted directly, solely by mechanical means in the RISCA GRANDE oil mill using the latest technologies (exclusion of oxidation) with olives from Spain.
The olive oil is filtered and bottled in a 10 L bag in box and a 3 L bag in tube.

REGION Portugal/Spain

OLIVE VARIETIES Arbequina

FORMS OF CONSUMPTION -

PRODUCT CHARACTERISTICS **Free Acidity:** 0.13 % Oleic acid
Peroxide Value: 6.2 (meq. O₂/kg)
K₂₃₂: 1,92
K₂₆₈: 0,13
Δ K: 0,00
Waxes: 60,0 mg/kg
FAEE: <2 mg/kg

SENSORIAL CHARACTERISTICS Medium fruity, well balanced in bitter and spicy.

NUTRITION FACTS

Nutrition Facts 100ml contain ca.:	
Energy	3400 kj / 813 kcal
Fat of which	92 g
-Saturates	12 g
-Mono-unsaturates	72 g
-Polyunsaturates	8 g
Carbohydrate of which:	0 g
-Sugars	0 g
Protein	0 g
Salt	0 g
Vitamin E	20 mg*

*167% of the Daily Reference Intake

TARGET AUDIENCE / POINTS OF SALE

- Retailers of organic and gourmet products
- Wholesale





TECHNICAL SHEET

OLIVAL DA RISCA EXTRA VIRGIN OLIVE OIL 2023/2024

Versão: 03
Data: 28-02-2024
Página: 2/2
Referência: I228

INGREDIENTS

Olives (100%)

BEST BEFORE

December 2025

STORAGE

Store the oil in a dark place and at room temperature.

RECOMMENDATION

Subcontracted transport at room temperature.

PACKAGING

UNIT			
Bag in Tube(1)	3l	Length (mm)	175
		Width (mm)	112
		Height (mm)	227
Barcode	560665100 0946	Gross Weight (kg)	2,93
		Net Weight (kg)	2,75
UNIT			
Bag in Box (2)	10l	Length (mm)	200
		Width (mm)	194
		Height (mm)	330
Barcode	5606651000 939	Gross Weight (kg)	9,75
		Net Weight (kg)	9,15

PALLET

UNITS	Nº OF LEVELS	Nº OF BOXES	GROSS WEIGHT	NET WEIGHT	TARE	LENGTH (mm)	WIDTH (mm)	HEIGHT (mm)
(1) 160	4	-	564	507	25	1200	800	1060
(2) 72	3	-	727	659	25	1200	800	1100